



HD-2XTE IRONCLAD

compact degausser



The fastest way to erase
magnetic hard drives.



10,000+ Gauss

Total erasure of magnetic hard drives with built-in field strength verification.



Easy and convenient

Compact, lightweight and quiet; no cooldown between cycles.



Superfast erasure

Each cycle takes just 7 seconds; erase 1000s of drives per hour!

IRONCLAD erasure verification system

- Complete **proof of erasure**

- **Image capture** of degaussed media

- Record serial number, operator ID, gauss field strength and erasure status

- Generate **audit-worthy Certificate of Erasure and Destruction Report**

- Export **JPG, PDF, CSV or Excel** formats to USB, ethernet or optical media

- **New user friendly** "Verification mode" or **high-speed** "Processing mode"



Why degauss?

Degaussing is **the best way to dispose of sensitive data** on end-of-life media, according to NIST's Guidelines for Media Sanitization.

It's **quicker, easier** and more **eco-friendly** than shredding, and enables bulletproof compliance with **GDPR & PCI-DSS** regulations.



Specifications

Part Number
IRONCLAD Includes

HD-2XTE IRONCLAD
Image capture system, touchscreen control head, reporting software, scanner and stand, stylus, 1 year software support, optional optical media burner
7 in. touchscreen, 16 GB storage capacity

Touch Control Head
Certifications

CE • TAA
1.0 Tesla (10,000 Gauss) nominal
~7 seconds (nominal)

Magnetic Field
Charge Time**Throughput**
Media

Up to 1920 (1.8 in.), up to 960 (2.5 in.), up to 240 (3.5 in.) drives per hour
Hard drives: Laptop, standard, network up to 1.25 in. in height
Tape media: All LTO, all DLT, AIT, 2590 Series, 8mm, and others

Power**Power Consumption**
Degausser System
Capacity (HxWxD)

HD-2XTE: 90~250VAC ±5%, 50/60 Hz • IRONCLAD: 90~240VAC, 47-440 Hz
Standby: 17W, Charge: 145W (avg), Erase: 17W • IRONCLAD: 15W
Continuous duty capacitive discharge
1.25 x 4.3 x 5.9 (in.), 31.8 x 108 x 148.6 (mm)

Temperature

41°F - 104°F (5°C - 40°C)

Humidity

10%H - 40%H without condensation

Weight

HD-2XTE: 34 lbs. (15.44 kg) • Control head: 4 lbs (1.8 kg)

Size (HxWxD)

HD-2XTE: 6 x 17.8 x 13.3 (in.) • Control head: 6.6 x 9.6 x 2.5 (in.)

Warranty

HD-2XTE: One-year manufacturer's limited warranty standard
IRONCLAD: One-year manufacturer's limited warranty standard
Scanner: Ninety-day manufacturer's limited warranty
by Garner Products, Inc.

Made in U.S.A.



Packages

Degauss / Destroy
/ Recycle

(DDR-25SSD IRONCLAD)
with PD-5E destroyer

**Data Eliminator**
Cart Package

(RCC-25SSD IRONCLAD)
Mobile cart with
PD-5E destroyer



Regulatory compliance

HD-2XTE helps you meet government and industry standards requiring erasure of sensitive data prior to disposal, including:

- CCPA (California Consumer Privacy Act)
- NSA/CSS/DOD Top Secret
- GDPR (General Data Protection Regulation)
- GLBA (Gramm-Leach-Bliley Act)
- HIPAA (Health Information Portability and Accountability Act)
- IRS 1075 • NIST SP 800-88r1 • TAA
- PCI DSS 3.2 (Payment Card Industry Data Security Standard)
- PIPEDA (Personal Information Protection and Electronic Documents Act)

