

varese
secure



HD-3XTLE IRONCLAD

high volume degausser

Heavy duty, high speed
magnetic hard drive erasure.

 **10,000+ Gauss**

Total erasure of magnetic hard drives with built-in field strength verification.

 **Easy and convenient**

Plugs into a standard wall outlet. Portable with optional MIL-SPEC case.

 **Heavy duty erasure**

3 second cycle and auto drive release; erase 1000s of drives per hour!

 **Why degauss?**

Degaussing is **the best way to dispose of sensitive data** on end-of-life media, according to NIST's Guidelines for Media Sanitization.

It's **quicker, easier** and more **eco-friendly** than shredding, and enables bulletproof compliance with **GDPR & PCI-DSS** regulations.

 varese-secure.co.uk  **01489 854 131**

IRONCLAD
erasure verification system

- Complete **proof of erasure**
- **Image capture** of degaussed media
- Record serial number, operator ID, gauss field strength and erasure status
- Generate **audit-worthy Certificate of Erasure and Destruction Report**
- Export **JPG, PDF, CSV or Excel** formats to USB, ethernet or optical media
- **New user friendly** "Verification mode" or **high-speed** "Processing mode"



Specifications

Part Number IRONCLAD Includes

HD-3XTLE IRONCLAD

Image capture system, touchscreen control head, reporting software, scanner and stand, stylus, 1 year software support, optional optical media burner
7 in. touchscreen, 16 GB storage capacity

Touch Control Head Certifications

CE • TAA

Magnetic Field Charge Time

1.0 Tesla (10,000 Gauss) nominal
~3 seconds (nominal)

Throughput Media

Up to 4,500 (1.8 in.) Up to 4,500 (2.5 in.) Up to 450 (3.5 in.) drives per hour
Hard drives: Laptop, standard, and network drives up to 1.7 in. in height
Tape media: All LTO, all DLT, 3490, 9940, 3592, AIT, and others

Power

Power Consumption Degausser System

HD-3XTLE: 220-240V \pm 5%, 50/60 Hz • IRONCLAD: 90~240VAC, 47-440 Hz
Standby: 53W, Charge: 188W (avg), Erase: 53W • IRONCLAD: 15W
Continuous duty capacitive discharge

Coercivity in NSA EPL-D Capacity (HxWxD)

Disk: 5000 Oe longitudinal and perpendicular recorded. Tape: 3000 Oe.
1.7 x 4.5 x 5.9 (in.), 43.2 x 114.3 x 148.6 (mm)

Temperature

41°F - 104°F (5°C - 40°C)

Humidity

10%H - 40%H without condensation

Weight

HD-3XTLE: 59 lbs. (27 kg) • Control head: 4 lbs (1.8 kg)

Size (HxWxD)

HD-3XTLE with slide: 18.9 x 22.8 x 13 (in.) • Control head: 6.6 x 9.6 x 2.5 (in.)

Warranty

HD-3XTLE • IRONCLAD: One-year manufacturer's limited warranty standard by Garner Products, Inc.

Made in U.S.A.



Packages

Degauss / Destroy / Recycle

(DDR-35SSD IRONCLAD)
with PD-5E destroyer
and SSD-1E add-on



Data Eliminator Cart Package

(RCC-35SSD IRONCLAD)
Mobile cart with
PD-5E destroyer and
SSD-1E add-on



Regulatory compliance

HD-3XTLE helps you meet government and industry standards requiring erasure of sensitive data prior to disposal, including:

- CCPA (California Consumer Privacy Act)
- DOD (up to Secret Classification)
- GDPR (General Data Protection Regulation)
- GLBA (Gramm-Leach-Bliley Act)
- HIPAA (Health Information Portability and Accountability Act)
- PCI Data Security Standard 3.2
- IRS 1075
- NIST SP 800-88r1
- PIPEDA (Personal Information Protection & Electronic Documents Act)

